



UD2 Series



PROFILE

A small, affordable, energy-efficient hardware platform that can be VESA mounted on the back of a monitor. The DVI-I port supports dual monitors with an optional Y-Cable and it can connect to common peripherals with its four USB ports.

FEATURES AND BENEFITS

- ▶ **Slim Design**
The perfect companion for any workplace due to the small form factor and the latest design.
- ▶ **VESA mountable** (optional)
Mountable on the back of a monitor with the optional available VESA bracket, ideal for space constrained environments.
- ▶ **Dualview support**
The DVI-I port offers the possibility to connect one digital and one analog monitor via the optional Y-Cable.
- ▶ **Excellent price performance**
Can run any firmware package at a competitive price.
- ▶ **No moving parts, e.g. cooling fans**
The absence of moving parts means the devices are almost noiseless and fail-safe with minimal heat generation.
- ▶ **Free evaluation:**
www.igel.com/evaluation

COLORS

- white
- dark blue
- black



FEATURE PACKS

1

Entry
UD2-130LX

4

Standard
UD2-430LX

PERIPHERAL INTERFACES





IGEL UD2 SPECIFICATIONS

SYSTEM

Available Operating Systems	IGEL Linux
Management	IGEL Universal Management Suite included
Form Factor	Standard
Processor	VIA Eden 500 MHz
Chipset	VIA VX855

MEMORY

RAM	1 GB
Flash Memory	1 GB

GRAPHICS

Chipset	VIA Chrome9
Video Memory	64–256 MB shared memory
Ports	1x DVI-I (DVI-to-VGA adapter included)
Supported Resolutions	1920 x 1200, Dualview

NETWORK

Ethernet	10/100 Base-T
----------	---------------

AUDIO

Chipset	AC97 compatible
Ports	Front: 1x line-out, 1x mic-in
Speakers	1x internal

PERIPHERAL INTERFACES

PS/2	1x keyboard
Serial	Optional, via USB-to-Serial adapter
Parallel	Optional, via USB-to-Parallel adapter
USB 2.0	4x back

DIMENSIONS

Device (D x W x H), upright	203 x 55 x 208 mm
Packaging (D x W x H), horizontal	268 x 112 x 264 mm
Weight	1.2 kg

ENVIRONMENT

Cooling	Fanless convection
Operating Temperature	0° to 40° C (vertical) 0° to 35° C (horizontal, with rubber feet)
Operating Humidity	10%–80%, non-condensing

POWER

Input	Auto sensing 100~240 VAC / 50~60 Hz
Power Supply	External
Power Consumption: Idle / Sleep Mode	9W / 2W

OPTIONS

VESA mount	For mounting on the back of a monitor
Rubber feet	For horizontal placement of the device
Dualview Y-Cable	For DVI-I to DVI-D + VGA. Connect two monitors
USB-to-Serial adapter	For connecting peripherals that require a serial port
USB-to-Parallel adapter	For connecting printers that require a parallel port
Shared WorkPlace	It allows user-dependent configuration based on setting profiles



After purchase, just register with us online, and all your IGEL thin clients UD2, UD3, and UD5 will be upgraded from a standard 2-year to a 5-year hardware warranty, according to our end customer hardware warranty declaration, at no additional cost. The UD9 series will be upgraded to a 3-year hardware warranty. The warranty upgrade does not cover any additional hardware options. IGEL is a registered trademark of IGEL Technology GmbH. All hardware and software names are registered trademarks of the respective manufacturers. Errors and omissions excepted. Subject to change without notice.

©10/2012 IGEL Technology | 85-EN-1-5 | WEEE-Reg.-Nr. DE 79295479

IGEL Technology GmbH | info@igel.com | www.igel.com

GERMANY
Augsburg · Bremen
info@igel.de
www.igel.de

UNITED KINGDOM
Reading
info@igel.com
www.igel.co.uk

FRANCE
Paris
france@igel.com
www.igel.fr

THE NETHERLANDS
Utrecht
benelux@igel.com
www.igel.nl

UNITED STATES
Cincinnati
info@igelamerica.com
www.igelamerica.com

CHINA
Hong Kong · Beijing · Shanghai
infochina@igel.com
www.igel.com/cn

SINGAPORE
info@igel.com
www.igel.sg

info@igel.com
www.igel.com



thin clients | development | services | solutions

Many functions. One device.